Saturn 5000 Fully Integrated, Highly Secure, Contactless Payment Reader

OTI's **Saturn 5000** is the ultimate contactless card reader powering contactless payment and loyalty programs, providing unsurpassed cost-to-performance results.

Supporting such major financial contactless programs, as **MasterCard's** *PayPass™*, the **Saturn 5000** reads data from a variety of sources, including credit cards and key fobs that comply with **ISO 14443 type A and B** (with Mifare support).

The **Saturn 5000** uses OTI's patented matched antenna technology to provide:

- More effective power consumption
- Reliable and stable communication
- Additional levels of security and encryption throughout the communication link.

The highly sophisticated, stylishly designed **Saturn 5000** reader supports programmable LEDs with buzzer to give user feedback for convenience. The **Saturn 5000** is designed to occupy minimum shelf space. It can be placed on the counter with various stands and fit different environments, drive thru, box office window and more.

Saturn 5000's plug-and-play design makes it easy to connect to your existing infrastructure and POS terminal, quickly upgrading it to contactless operations without disrupting your on going business operations.







Interface Options to POS

- RS232 Interface
- RS485 Interface
- USB Interface
- MSR Coil Interface
- MSR Head Interface
- MSR PS2 Interface
- MSR RS232 Interface

Standards

- Compliant to ISO 14443 Type A & B (with Mifare support)
- FCC part 15 and EN 301 489-3
- PayPass compliant

Secure and Flexible Platform

- Integrated, sophisticated Smart Card Operating System on board
- Flexible, software-configurable design
- On-board EMV2000 compliant SAM support
- High security encryption system (DES/RSA)
- In-system programming of reader firmware to 128KB flash memory via standard RS232 / RS485 / USB communication

General Features

- Dimensions: 6.4" (163mm) H x 4.2" (107mm) W x 0.75" (19mm) D
- Proximity range up to 4 inches (10 cm)
- 4 In board Indicator LEDs and 4 programmable LEDs.
- Power input from 6.5 to 15VDC / 1.35W

www.otiglobal.com

USA



On Track Innovations, Ltd. ZHR Industrial Zone P.O. Box 32

Rosh Pina, 12000 Israel Tel: +972-4-6868000

Fax: +972-4-6938887 info@otiglobal.com

OTI America 1601 S. De Anza Blvd. Suite 201 Cupertino, CA 95014

Tel: 408-252-0333 Fax: 408-252-8414 info@otiamerica.com

OTI Africa

10th Floor, Park on Long 64 Long Street Cape Town, 8001 South Africa Tel: +27-21-422-1940 Fax: +27-21-422-1969 chambly@iafrica.com



side view



Discount Merchant Services

Razor Quote 1(877)729-6778

